

| | | | |
|----|-------------|----|-----------------|
| 型號 | CT-DHC3L6NL | 名稱 | 數字顯示時間繼電器 Timer |
|----|-------------|----|-----------------|

產品外觀



- DIN48X24mm標準面板尺寸,可擴展成50x60mm
- 內部自帶電源,不須外接
- 復歸信號不應長時間接通,以免浪費內部電池
- 累計時精度高
- LCD顯示,顯示大而清晰
- 面板復歸帶鎖定,防止錯誤操作
- 無機械磨損,壽命長
- 電源:內部電源
- 電池壽命: ≥ 6 年
- 顯示字高:6.7mm
- 累計時誤差: $\leq 0.002\%$
- 接點接通最大電阻 $\leq 10K\Omega$ (計數ON)
- 接通斷開最小電阻 $\geq 500K\Omega$ (計數OFF)
- 輸入最大殘餘電壓:0.5V
- 最小信號脈寬 ≥ 0.2 秒
- 重量:約60g
- 開孔尺寸:22.2x45mm
- 復歸方式:外部端子復歸
- 使用環境溫度:-10~40°C

- DIN 48x24mm Standard Faceplate Area, can expand to 50X60mm
- Internal power source, no need for external power
- Reset signal should not be applied for a long time so that internal battery will not be wasted.
- Very accurate timer.
- LED display, large and clear.
- Reset and Lock, to prevent errors in operating
- No mechanical wear out, long lifetime
- Power: Internal power.
- Battery Life-Expectancy: ≥ 6 Years
- Number Display Height: 6.7mm
- Timer Error: $\leq 0.002\%$
- ON/OFF maximum resistance $\leq 10K\Omega$ (Counter ON).
- ON/OFF minimum resistance $\geq 500K\Omega$ (Counter OFF).
- Maximum Residual Voltage 0.5V
- Weight: Approximately 60g
- Dimension of Mounting Hole: 22.2X45mm
- Reset Method: External Button
- Operating Temperature: -10~40 Degrees Celsius

